

RCKB

Junction box



FIRE SAFETY



13/09/2017

www.bevent-rasch.com



BEVENT RASCH

AIR SOLUTIONS – FOR A BETTER TOMORROW



Junction box RCKB



RCKB-1



RCKB-U



RCKB-T

Use

Junction box RCKB is used to inter-connect the connection and installation cables.

RCKB-1

contains 5 terminal blocks and is completely adequate for use of Bevent Rasch fire/combustion gas dampers, since it is equipped with actuator with internally coupled thermal sensor incl. switch for manual testing as standard.

RCKB-U

is used for fire/combustion gas dampers and combustion gas dampers with 24V actuators without thermal sensor. The box is prepared for connection of fire thermostat or separate thermal sensor that deplete the supply voltage 24V to the connected actuators.

RCKB-T

is equal to RCKB-U but equipped with push button for manual testing of dampers.

RCKB is designed for surface installation.

Specification

Example: **Junction box RCKB-1**

5 terminal blocks	= 1
Without test button	= U
With test button	= T

Technical data

	RCKB-1	RCKB-U/T
Voltage:	max 250V	24V
Protection class:	IP 54	IP 54
Terminal blocks:	max 4 mm ²	max 2,5 mm ²
Ambient temperature:	-30 to +70°C	-30 to +70°C
Dim. a x w x h	84x84x40 mm	84x84x40 mm

Wiring diagram

